

IN THE CLAIMS

Please amend the claims as follows:

1. (Currently Amended) A treatment apparatus, comprising:

a first hermetic chamber having a first opening;

a tube capable of inserting into the first opening, and the tube having a second opening on ~~a side facing the first hermetic chamber~~ an end of the tube and a third opening on the tube, the end facing the first hermetic chamber; and

a first hermetic door, placed outside the first hermetic chamber, capable of opening and closing the first opening, the first hermetic door being positioned between the second opening and the third opening such that the first hermetic door is shielded from the first hermetic chamber by the tube when insertion of the tube into the first opening is completed.

2. (Previously Presented) The treatment apparatus as set forth in claim 1, comprising:

an exhaust system for exhausting the first hermetic chamber via the second opening and the third opening of the tube when the tube is inserted into the first opening.

3. (Previously Presented) The treatment apparatus as set forth in claim 2,

wherein the first hermetic chamber maintains a vacuum state when the first hermetic door is at a closing position, while the tube is allowed to be replaced.

4. (Previously Presented) The treatment apparatus as set forth in claim 2,

the exhaust system exhausts the first hermetic chamber when the first hermetic door is at an opening position, and the exhausting system is isolated from the first hermetic chamber when the first hermetic door is at a closing position so that the tube is allowed to be replaced.

5. (Previously Presented) The treatment apparatus as set forth in claim 1, comprising:

a means for cooling the tube when the tube is inserted into the first opening.

6. (Previously Presented) The treatment apparatus as set forth in claim 1, further comprising:

a means for regulating a temperature in the first hermetic chamber when the first hermetic door is at an opening position and a closing position.

7. (Previously Presented) The treatment apparatus as set forth in claim 1, further comprising:

a means, placed along the inserting direction of the tube, for guiding an inserting operation of the tube.

8. (Previously Presented) The treatment apparatus as set forth in claim 1, wherein the first hermetic chamber has a plurality of the first openings, the plurality of the first openings are linearly arranged, and the tube and the first hermetic door are provided at each of the first openings.

9. (Previously Presented) The treatment apparatus as set forth in claim 1, wherein a plurality of the first hermetic chambers are linearly arranged, said plurality of the first hermetic chambers being portioned off by openable and closeable partitions.

10. (Previously Presented) The treatment apparatus as set forth in claim 1, further comprising:

a second hermetic chamber adjoining the first hermetic chamber with the first hermetic door therebetween, wherein the tube is inserted into the first opening of the first

hermetic chamber from the second hermetic chamber.

11. (Previously Presented) The treatment apparatus as set forth in claim 10, further comprising:

an exhaust system connected to the first hermetic chamber via the second hermetic chamber.

12. (Previously Presented) The treatment apparatus as set forth in claim 11, wherein the third opening of the tube and the exhaust system are hermetically connected when the tube is inserted into the first opening of the first hermetic chamber.

13. (Previously Presented) The treatment apparatus as set forth in claim 10, further comprising:

a means for performing pressure regulation in a space between the tube and the second hermetic chamber so that a pressure in the space is higher than a pressure in the first hermetic chamber when the tube is inserted into the first opening of the first hermetic chamber.

14. (Previously Presented) The treatment apparatus as set forth in claim 10, further comprising:

a means for performing pressure regulation in the first hermetic chamber so that a pressure in the first hermetic chamber is lower than a pressure in a space between the tube and the second hermetic chamber and higher than a pressure in the tube when the tube is inserted into the first opening of the first hermetic chamber.

15. (Previously Presented) The treatment apparatus as set forth in claim 13, wherein the means for performing pressure regulation has a means for supplying a

carrier gas to a space between the tube and the second hermetic chamber.

16. (Previously Presented) The treatment apparatus as set forth in claim 11, further comprising:

a filter means placed between the second hermetic chamber and the exhaust system.

17. (Original) The treatment apparatus as set forth in claim 16,
wherein the filter means includes at least a wet filter.

18. (Previously Presented) The treatment apparatus as set forth in claim 10,
wherein the tube is removable, and the second hermetic chamber has a second
hermetic door that is hermetically openable and closeable for replacing the tube with a second
tube.

19. (Previously Presented) The treatment apparatus as set forth in claim 10, further
comprising:

a means for regulating a temperature in the second hermetic chamber.

20. (Previously Presented) The treatment apparatus as set forth in claim 10, further
comprising:

a means for supplying a non-oxidizing gas to the second hermetic chamber.

21-36. (Canceled)